

Embedded Wireless Networking for Automotive CPS: Probabilistic Guarantees and Implications

Hongwei Zhang, Le Yi Wang, George Yin
Wayne State University
{hongwei, lywang, gyin}@wayne.edu

1 Embedded wireless networking for automotive CPS

Today's vehicles are much more than a mechanical device, and complex systems of sensing, computing, communication, and control are ubiquitously deployed to serve as the intelligent nerve systems of vehicles. For instance, the number of electronic control units (ECUs) is well over 70 in today's high-end vehicles, and these ECUs process up to 2,500 signals (i.e., elementary information such as vehicle speed) and support up to 500 features such as brake-by-wire and active safety [6]. The increasing number of ECUs and control systems deployed in vehicles pose significant challenges to the scalability of vehicular communication system, which is a basic element of automotive cyber-physical systems (CPS), and it has become a common practice to deploy multiple communication networks (such as CAN networks) within a single vehicle. These many vehicular networks are starting to add significant weight to vehicles and reduce gas efficiency. For instance, it has been shown that wiring harness is the heaviest, most complex, bulky, and expensive electrical component in a vehicle and it can contribute up to 50 kg to the vehicle mass [4].

To address the aforementioned challenges, wireless networks such as wireless, embedded sensor networks have been envisioned to be a basic element of future automotive CPS [4]. Besides reduced weight and thus improved gas efficiency, wireless networks also enable communication and coordination among vehicles on the road for purposes such as active safety. It is thus expected that wireless networks be ubiquitously deployed and serve as a basic element of both intra-vehicle and inter-vehicle CPS. In supporting mission-critical tasks, automotive CPS pose stringent requirements on the reliability and timeliness of wireless messaging. Nonetheless, wireless messaging is subject to inherent uncertainties and dynamics within the system itself and from the environment in automotive CPS. In what follows, we first examine the challenges that systems and environmental dynamics pose to embedded wireless networking in automotive CPS, then we present the implications and research directions.

2 Complex dynamics and uncertainties in wireless automotive CPS

Within a system, wireless communication assumes complex spatial and temporal dynamics due to unpredictable channel fading, network topology constantly changes in inter-vehicle networks due to vehicle mobility, network traffic pattern can be dynamic due to event-triggered data traffic and varying applications (e.g., adaptive control logic), and application requirements on messaging quality (e.g., throughput, latency, and/or reliability) may also vary over time and across different applications. Moreover, different dynamics may well interact with one another to yield complex behavior. For instance, dynamics in network traffic pattern introduce dynamics in co-channel interference and thus dynamics in wireless link properties (e.g., reliability), which in turn affect link estimation and messaging in wireless networks [9, 11].

From the environment, a wide variety of factors can affect the behavior of wireless messaging. Environmental factors such as temperature and humidity can affect wireless communication, electromechanical equipments in vehicles can create complex multipath environments, moving objects (humans in a vehicle or surrounding vehicles) may introduce unpredictable dynamics to wireless communication, co-existing wireless networks may interfere with message passing, and malicious attackers may try to jam a network.

Unlike the faults/perturbations considered in most traditional fault-tolerant systems, dynamics in wire-

less automotive CPS occur at multiple timescales at the same time. At longer timescales, there exist temporal link dynamics due to changing environment (e.g., temperature, humidity), long-lived traffic flows may come and go, and application QoS requirements may change. In the mean time, there exist dynamics that happen at very short timescale (e.g., in milliseconds), and they include fast channel fading, bursty traffic variation, high node mobility, and transient link perturbations due to human/object movement.

Besides differences in root-causes and frequencies, dynamics also differ in terms of controllability. Some dynamics are controllable, whereas others are uncontrollable. For instance, co-channel interference from concurrent transmitters can be controlled, so is network traffic pattern. On the other hand, many dynamics are uncontrollable, and they include dynamic wireless channel fading, interference from co-existing networks or jamming attackers, as well as unpredictable sensing events.

These multi-dimensional dynamics introduce complex uncertainties in wireless automotive CPS, and they challenge the traditional wisdom of network system design. To enable dependable messaging and predictable behavior of wireless automotive CPS, therefore, it is important to re-think systems design to address these complex dynamics. Given the potential resource constraints of wireless automotive CPS (e.g., limited channel bandwidth, memory, and processing power), the solutions have to be light-weight and efficient too. To this end, we explore in the next section research directions that will help lay a solid foundation in addressing these challenges of wireless automotive CPS.

3 Experimental infrastructures and probabilistic guarantees

High-fidelity experimental infrastructures. Due to inherent uncertainties of systems and environmental dynamics as well as their interactions, empirical measurement study is crucial for understanding the complex behavior of wireless automotive CPS, for instance, for extracting models of wireless interference and for evaluating network protocols. The research community have built various wireless and sensor network testbeds such as NetEye [7] and Kansei [5]. While these testbeds have proven instrumental in general wireless and sensor network research and education, they do not focus on supporting research and education in wireless automotive CPS and CPS in general. To facilitate wireless automotive CPS research and education, we need to develop experimental infrastructures that capture the challenges and complexities of mission-critical automotive CPS, including the interactions within the ecosystem of different wireless networks (e.g., DSRC, 802.15.4, and ultra-wideband) and different sensing substrates. To provide high-fidelity, flexible wireless automotive CPS experimental infrastructures, we need to incorporate measurement facilities with simulation/emulation tools so that we can exploit the complete spectrum of experimental design and analysis. Apart from the NSF CPS program, the NSF Global-Environment-for-Network-Innovations (GENI) initiative [2] has also been developing infrastructures for mobile, wireless network applications (including vehicular network applications [1]). The US Department of Transportation (DOT) has built national testbeds for vehicle-infrastructure-integration, and they are in the process of phasing out the next-generation experimental infrastructures of connected vehicles [3] and intelligent transportation system in general. Therefore, we need to explore potential synergy between the CPS program and these related programs in establishing an instrumental experimental platform for wireless automotive CPS and CPS in general.

Probabilistic guarantees. To enable predictable messaging for wireless automotive CPS, we need to take a holistic approach to addressing the impact of complex dynamics on wireless messaging. More specifically, we need to integrate the life cycle of requirement engineering, capacity planning, protocol and system design, system analysis and performance evaluation to effectively take into account the dynamics and uncertainties in the design, analysis, and evaluation of automotive CPS. In addressing the dynamics and uncertainties in wireless automotive CPS, we should also try to take advantage of the unique properties of these CPS systems. For instance, the potentially periodic, predictable control data samples may enable effective scheduling mechanisms for dealing with co-channel interference; the availability of vehicle power sources may relieve system design from severe energy constraint as seen in classical low-power sensor networks. In addressing the dynamics and uncertainties, we should also leverage the new advances in the modeling and protocol design for wireless networked sensing and control, for instance, interference modeling for

distributed protocol design [10] and multi-timescale approaches to real-time data delivery [8].

Due to the dynamics and uncertainties in wireless automotive CPS, we expect wireless communication properties (e.g., reliability, delay, and throughput) to be inherently probabilistic, thus any guarantees on wireless communication properties tend to be probabilistic in nature too. Since traditional networked control design methods have been mostly based on deterministic (worst-case) delay, there is a dire need for new paradigms of networked control that can effectively integrate with probabilistic communication quality guarantees.

References

- [1] GENI experimental infrastructures for vehicular sensing and control networking. <http://www.cs.wayne.edu/~hzhang/group/projects.html>.
- [2] NSF GENI program. <http://www.geni.net/>.
- [3] USDOT connected vehicle testbeds. <http://www.its.dot.gov/testbed.htm>.
- [4] T. Elbatt, C. Saraydar, M. Ames, and T. Talty. Potential for intra-vehicle wireless automotive sensor networks. In *IEEE Sarnoff Symposium*, 2006.
- [5] E. Ertin, A. Arora, R. Ramnath, M. Nesterenko, V. Naik, S. Bapat, V. Kulathumani, M. Sridharan, H. Zhang, and H. Cao. Kansei: A testbed for sensing at scale. In *IEEE/ACM IPSN*, 2006.
- [6] H. Gharavi, K. V. Prasad, and P. Ioannou. Scanning advanced automobile technology. *Proceedings of IEEE*, 95(2):328–333, 2007.
- [7] X. Ju, H. Zhang, and D. Sakamuri. NetEye: A user-centered wireless sensor network testbed for high-fidelity, robust experimentation. *International Journal of Communication Systems (Wiley)*, 25(9):1213–1229, 2012.
- [8] X. Liu, H. Zhang, Q. Xiang, X. Che, and X. Ju. Taming uncertainties in real-time routing for wireless networked sensing and control. *IEEE Transactions on Smart Grid (TSG)*, 2012.
- [9] H. Zhang, A. Arora, and P. Sinha. Link estimation and routing in sensor network backbones: Beacon-based or data-driven? *IEEE Transactions on Mobile Computing*, 8(5):653 – 667, May 2009.
- [10] H. Zhang, X. Che, X. Liu, and X. Ju. Adaptive instantiation of the protocol interference model in wireless networked sensing and control. *ACM Transactions on Sensor Networks (TOSN)*, in press.
- [11] H. Zhang, L. Sang, and A. Arora. Comparison of data-drive link estimation methods in low-power wireless networks. *IEEE Transactions on Mobile Computing*, 9(11):1634–1648, November 2010.